

***ZERO** alcohol tolerance policy. Oxford Fair reserves the right to inspect coolers

*All cars **MUST** be 1985 and newer

*4 cylinder division **MUST** have 105” or under wheel base

*Ladies division **MUST** have 108” or under wheel base

*Ladies may use 4, 6 or 8 cylinder vehicles

*Full size vehicles **MUST** have 105” or more wheel base, may have 6 or 8 cylinders

*Mini vans may be 4 or 6 cylinders

Mini Vans: **NO** All-wheel drives or composite bodies (such as Lumina APV’s or Pontiac Transports)

***NO** hearses or ambulances will be allowed

***NO** valve stem protectors

*Stock tires **MUST** be used – **NO** hard rubber or snow tires – **NO** liquid in tires---- air only

*Water in radiators only

*Gas engines only (**NO** diesel engines)

*Hoods and trunks **MUST** have locking latches removed and be tied down with rope **ONLY**. All cars **MUST** have trunk lids on **AND** tied down

*A 12” hole **MUST** be cut into hood and trunk lid (in case of fire)

*Fuel tanks may be replaced with fuel cells or smaller tanks. All tanks **MUST** be securely fastened **AND** covered or firewall between fuel cell/tank and driver

*A shut off switch **IS NOT** mandatory but may be added at driver discretion

***NO MORE THAN 5 GALLONS OF GAS ONLY IN FUEL TANKS**

*One (1) automotive battery per car...Batteries may be moved to the inside of the vehicle, but **MUST** be covered and bolted down...holes in the windshield **MUST** be in the right had corner and taped well

*Vehicle **MUST** remain as manufactured. **NO** notching, cutting, use of a hammer/sledgehammer/hammer, bending or reinforcement of any other kind other than reinforcement of Driver’s door

*All glass **MUST** be removed **EXCEPT** for windshields. If windshied is removed, it **MUST** be replaced with screen or Lexan

*All chrome, hub caps, antennas, wheel weights and exterior plastic **MUST** be removed. Plastic bumpers and side mirrors **MUST** be removed

*Seat belts **MUST** be functional **AND** worn at all times

***Broken seats will result in IMMEDIATE DISQUALIFICATION**

***Foam padding in driver's door is MANDATORY**

***NO DRIVER'S DOOR HITS WILL BE TOLERATED**

***Driver's door MUST be chained or welded. Passenger's door can be chained or have four (4) 1 inch welds to hold the door shut. MAXIMUM 1/4" steel plate may be used on the outside of the driver's door. May have cage or piping welded inside of car for driver's safety. MUST be professionally welded**

***Helmets and goggles or face shields MUST be worn WITH chin straps fastened at all times. Long sleeve shirt and pants MUST be worn. Firesuits are highly recommended. Must wear full shoes or boots, NO Sandals, clogs or barefeet**

***NO offensive, lewd or vulgar lettering or pictures allowed**